1000 Industrial Dr. Unit 1C
Bensenville, IL 60106
Phone: 630-350-1770 fax: -0315
info@arcomech.com

Fire Damper Quote/Order Form

abi air balance

Prefco

Job Name _____ PO# _____

SHIP TO _____ Address _____

Fax your damper schedule to:
630-350-0315

Tag	Qty	Size		Vert or Horiz	1 1/2 or 3 HR	static or dynamic	Type A or B	Sleeve		Notes
		W	H					ga	length	

- Centerline of closed damper will be in the middle of the sleeve, unless specified differently. Can be as close as 2" from edge. Flanged sleeves available for mounting grille directly on sleeve.
- Sleeves are available in 14/16/18/20/22 gauge—in any length
- Mounting angles are required (UL) on both sides of sleeves less than 16 gauge, single sided angles OK for thicker gauges
- Link temps are typically 165 degF (212 is also available)
- Type A = curtain style fire damper with blades stacked in air stream. We recommend PREFCO's LPB style damper, this is a Type A damper with Type B performance. Saves $.
- Type B dampers have blades out of air stream and thus a lower press drop across the damper compared to Type A.
- Type C dampers are available. Type C dampers have frame AND blades out of air stream = a slightly oversized damper compared to duct.
- PREFCO's vertical dynamic damper does NOT require a spring. The only mfg able to do so in the industry. Saves $
- Round and oval dampers are available
- Unless stated ARCO will select Prefco or Air Balance to best fit your requirements. prefco-hvac.com airbalance.com
- QUICKSHIP's of 24 Hr and 3 days available. Standard lead time is 15 days.